

AHD PTZ

AHD SPEED DOME AP4102CI



Feature

- Real time transmission, no video loss
- High definition 1080P, 10X Zoom
- Long distance transmission up to 300 meters
- Multiple languages for OSD menu / IR distance 50M
- 4" Total Metal body construction, IP66 rate protection
- IR illumination & power consumption is variable dependent on zoom factor

Camera	
Image Sensor	1/3" progressive scan CMOS
Effective Pixels	1080P (1920 x 1080)
Total Pixels	2.0MP
Optical Zoom	10x optical zoom
Focal Length	f = 5.0mm ~ 50.0mm
Day& Night	IR-CUT
Focus Mode	Auto / Manual
S/N Ratio	more than 50dB
IR Leds	
IR Leds	6 high power array IR leds
IR Range	50m
IR Action Mode	Auto / Manual / Camera
IR Led Power	20W
Pan & Tilt	
Pan Range	360° endless
Pan Speed	Pan Manual Speed: 0.05°-300°/s, Pan Preset Speed:300°/s
Tilt Range	-10°-90° (Auto Flip)
Tilt Speed	Tilt Manual Speed: 0.01°-120°/s, Tilt Preset Speed:120°/s
Number of Preset	127
Group	8 patrols, up to 16 presets per patrol
Swing	8 scans with settable left and right boundaries
Pattern	4 patterns, up to 500 instructions per pattern
Pan scan	1 pan scan (running speed can be set)
Tilt scan	1 tilt scan (running speed can be set)
General	
Power Box	Optional
Power Supply	DC12V/3A
Power Consumption	25W
Working Temperature	-35°C ~ 55°C
Humidity	90% or less (No Condensing)
Protection Level	IP66 standard , Level 2 lightning protection, 3KV surge protection
Mounting	Various mounting modes option: wall-mount, pendant-mount
Weight (approx.)	3.5kg
Accessories	Wall-mount bracket & Power

Specifications subject to change without notice.