

ELECTRICAL METALLIC TUBING (EMT)

Electro-galvanized



UL Listed
E481360

ANSI C80.3
UL 797

TRADE SIZE		NOMINAL OUTSIDE Ø		NOMINAL WALL THICKNESS		UNIT LENGTH		WEIGHT OF 10 UNIT LENGTHS (KG)
in.	mm.	in.	mm.	in.	mm.	mm.	ft.	
1/2	16	0.706	17.93	0.042	1.07	3050	10	12.95
3/4	21	0.922	23.42	0.049	1.25	3050	10	19.75
1	27	1.163	29.54	0.057	1.45	3050	10	29.00
1-1/4	35	1.510	38.35	0.065	1.65	3050	10	43.10
1-1/2	41	1.740	44.20	0.065	1.65	3050	10	49.95
2	53	2.197	55.80	0.065	1.65	3050	10	63.55

INTERMEDIATE METAL CONDUIT (IMC)

Hot-dipped galvanized inside and outside

Threaded at both ends with one coupling at one end, thread protector on the other.



UL Listed
E479354

ANSI C80.6
UL 1242

TRADE SIZE		NOMINAL OUTSIDE Ø		NOMINAL WALL THICKNESS		UNIT LENGTH			WEIGHT OF 10 UNIT LENGTHS (KG)
in.	mm.	in.	mm.	in.	mm.	mm.	ft.	±1/4 in.	
1/2	16	0.815	20.70	0.078	1.97	3030	9	11-1/4	28.12
3/4	21	1.029	26.14	0.083	2.10	3030	9	11-1/4	38.10
1	27	1.290	32.77	0.093	2.35	3025	9	11	53.98
1-1/4	35	1.638	41.59	0.095	2.41	3025	9	11	71.67
1-1/2	41	1.883	47.82	0.100	2.54	3025	9	11	88.00
2	53	2.360	59.93	0.105	2.67	3025	9	11	116.12
2-1/2	63	2.857	72.57	0.150	3.81	3010	9	10-1/2	200.04
3	78	3.476	88.29	0.150	3.81	3010	9	10-1/2	246.30
3-1/2	91	3.971	100.86	0.150	3.81	3005	9	10-1/4	285.31
4	103	4.466	113.44	0.150	3.81	3005	9	10-1/4	317.52

RIGID STEEL CONDUIT (RSC)

Hot-dipped galvanized inside and outside

Threaded at both ends with one coupling at one end, thread protector on the other.



UL Listed
E485208

ANSI C80.1
UL 6

TRADE SIZE		NOMINAL OUTSIDE Ø		NOMINAL WALL THICKNESS		UNIT LENGTH			WEIGHT OF 10 UNIT LENGTHS (KG)
in.	mm.	in.	mm.	in.	mm.	mm.	ft.	±1/4 in.	
1/2	16	0.840	21.34	0.104	2.64	3030	9	11-1/4	35.80
3/4	21	1.050	26.67	0.107	2.72	3030	9	11-1/4	47.60
1	27	1.315	33.40	0.126	3.20	3025	9	11	69.40
1-1/4	35	1.660	42.16	0.133	3.38	3025	9	11	91.20
1-1/2	41	1.900	48.26	0.138	3.51	3025	9	11	112.90
2	53	2.375	60.33	0.146	3.77	3025	9	11	150.60
2-1/2	63	2.857	73.03	0.193	4.90	3 010	9	10-1/2	239.00
3	78	3.500	88.90	0.205	5.21	3010	9	10-1/2	309.60
4	103	4.500	114.30	0.225	5.72	3005	9	10-1/4	441.00