



## CEILING SPEAKER



### CSL-623

- Frameless Design
- 6" Coaxial w/ Back Cover
- Impedance: 7.2 ohms
- Sensitivity: 93dB
- Freq. Resp.: 90Hz-20KHz
- 100V TAP 10W, 5W, 2.5W



### CSL-605

- Frameless Design
- 6" Full Range
- Impedance: 7.2 ohms
- Sensitivity: 93dB
- Freq. Resp.: 100Hz-16KHz
- 100V TAP 6W, 3W



### CSL-805

- Frameless Design
- 8" Full Range
- Impedance: 7.2 ohms
- Sensitivity: 94dB
- Freq. Resp.: 95Hz-16KHz
- 100V TAP 10W, 5W



### COAX-6

- Frameless Design
- 6" Coaxial
- Impedance: 8 ohms
- Sensitivity: 88dB
- Freq. Resp.: 60Hz-20KHz
- Power Tap Switch
- 15W, 10W, 5W, 2.5W
- RMS Power: 50W



### COAX-8

- Frameless Design
- 8" Coaxial
- Impedance: 8 ohms
- Sensitivity: 89dB
- Freq. Resp.: 50Hz-20KHz
- Power Tap Switch
- 15W, 10W, 5W, 2.5W
- RMS Power: 80W

