



## CONFERENCE SYSTEM



### AM-300

#### Conference system main unit

Provides DC power to all contribution units  
 Simultaneous active delegate units  
 Din connector for additional extension unit  
 AC power requirement: 220V, 60Hz  
 Frequency response: 20Hz-18KHz  
 Distortion @ 1KHz: <0.3%



### LM-500U

#### Conference system main unit

Record & Play function thru USB/SD with FM tuner.  
 Equipt with 3 groups for system connecting  
 workable for 20 unit for each group  
 Single, multiple and many groups can be use  
 simultaneously  
 Rack mountable main unit,  
 include rack mounted ears  
 Output level LED indicator  
 Line volume for the unit source  
 Mic volume for the external mic connection  
 Master volume control the Line mic level  
 Balance XLR output  
 Extention to other main unit in case will use  
 more than 60pcs conference mic

### AM-300C

#### (Chairman's Unit)

Push button switch for MIC ON/OFF  
 Priority button to override all active delegates units  
 Unidirectional electret condenser microphone  
 Red ring luminate to identify live unit  
 Frequency response: 70Hz-15KHz  
 S/N ratio at 1mV, input level -95dB  
 Sensitivity: -47±3dB  
 Microphone stem length: 41cm  
 Dual shielded captive cable



### LM-501

#### (Chairman's Unit)

- Priority buttons
- Mic ON/OFF buttons
- Built-in 2W speaker
- Volume control
- Unidirectional condenser mic
- Red light indicate mic is ON



### AM-300D

#### (Delegate's Unit)

Push button switch for MIC ON/OFF  
 Unidirectional electret condenser microphone  
 Red ring luminate to identify live unit  
 Frequency response: 70Hz-15KHz  
 S/N ratio at 1mV, input level -95dB  
 Sensitivity: -47±3dB  
 Microphone stem length: 41cm  
 Dual shielded captive cable



### LM-502

#### (Delegate's Unit)

- Mic ON/OFF buttons
- Built-in 2W speaker
- Volume control
- Unidirectional condenser mic
- Red light indicate mic is ON





## CONFERENCE SYSTEM



### QM-900U

Conference system main unit

- Record & Play function thru USB/SD with FM tuner.
- Equip with 3 groups for system connecting workable for 20 unit for each group
- Single, multiple and many groups can be use simultaneously
- Rack mountable main unit, include rack mounted ears
- Output level LED indicator
- Line volume for the unit source
- Mic volume for the external mic connection
- Master volume control the Line mic level
- Balance XLR output
- Extension to other main unit in case will use more than 60pcs conference mic



### TC-2000

- Dual UHF True Diversity Wireless Microphone
- Each receiver have 20 Groups, 40 UHF frequencies can be selected.
- Dual Antenna per channel (quad antenna) True Diversity receiving system.
- 1U rack unit design.
- Big LCD display for easy viewing, display light change when synchronized.
- Balance XLR and unbalance audio output.
- Volume digital control system, soft touch button control, easy to operate.
- The receiver can display the transmitter's battery status, so it's convenient to the operator to supervise the battery consumption.
- Automatic Scan Channel function.



### QM-900C

(Chairman's Unit)

- Priority buttons
- Mic ON/OFF buttons
- Built-in 2W speaker
- Volume control
- Unidirectional condenser mic
- Red light indicate mic is ON



### QM-900D

(Delegate's Unit)

- Mic ON/OFF buttons
- Built-in 2W speaker
- Volume control
- Unidirectional condenser mic
- Red light indicate mic is ON



Beltpack



Lapel Mic

