

Metal A&C Readers

MR100/MR101

Metal Case & IP66

Outdoor Installation Allowed



MR100/MR101 are contactless card reader which featured by its metal casing design, strong durability, dismantle & pry protection, simple wiring and Wiegand 26/34bits output.

Features:

- IP66 waterproof
- Operating voltage: 9-18V DC / 9-24V DC
- Wiegand outputs 26/34bits
- Metal casing design
- Operating temperature: - 40°C ~ 60°C
- Reading distance: 3 ~ 8cm

Specifications:

Model	MR100	MR101	
Operating Voltage	9-18V DC	9-24V DC	
Operating Current	≤25mA	≤35mA	
Card Frequency	125KHz /13.56MHz	125KHz /13.56MHz	
Card Reading Distance	3 ~ 8cm	Size	103*48*19mm
Wiegand Output	26/34bits	Weight	300g
Operating Temperature	- 40°C ~ 60°C	Waterproof Rate	IP66
Operating Humidity	10% ~ 85%	Wire Length	45mm±10mm

ERP Code:

MR100[ID]	125KHz Blank logo	X02101012
MR100[C]	13.56MHz Blank logo	X02101071
MR101[C]	13.56MHz Blank logo	X02101046
MR101[ID]	125KHz ZKTeco logo	X02102040
MR101[C]	13.56MHz ZKTeco logo	X02101059

