



PLASTIC MOLDED SPEAKER

EON SERIES



EON-8

- 8" 2 Way Bass Reflex
- Low 1.5" Vcoil
- Hi 1" Vcoil
- 200 Watts
- 8 Ohms
- 96dB
- 50Hz-20KHz



EON-12

- 12" 2 Way Bass Reflex
- Low 2" Vcoil
- Hi 1.5" Vcoil
- 500 Watts
- 8 Ohms
- 98dB
- 45Hz-20KHz



EON-10

- 10" 2 Way Bass Reflex
- Low 2" Vcoil
- Hi 1" Vcoil
- 300 Watts
- 8 Ohms
- 97dB
- 48Hz-20KHz

EON-8A

- 100 Watts Amplifier
- USB/FM/BT Function
- Mic Input
- RCA Input
- Line Input/Output
- Speaker out
- 39(H) x 25(W) x 21(D)cm

EON-12A

- 250 Watts Amplifier
- USB/FM/BT Function
- XLR Line Input/Output
- 2 Mic Input
- RCA Input
- Speaker out
- 57.5(H) x 33(W) x 30(D)cm

EON-10A

- 150 Watts Amplifier
- USB/FM/BT Function
- XLR Line Input/Output
- Mic Input
- RCA Input
- Speaker out
- 49(H) x 33(W) x 26.5(D)cm



EON-15

- 15" 2 Way Bass Reflex
- Low 2.5" Vcoil
- Hi 1.7" Vcoil
- 800 Watts
- 8 Ohms
- 100dB
- 40Hz-20KHz



EON-15D

- Class D Amplifier 500Watts
- DSP Management Control
- USB/BT Function
- RCA / XLR Line Input
- 1 Mic / Line Input (switchable)
- XLR Line Output
- 67.5 (H) x 39 (W) x 34.5(D)cm





PLASTIC MOLDED SPEAKER

PORTABLE PA SERIES



NEW!

JL-15PA

- 15" 2 Way Bass Reflex
- Low 2" Vcoil
- Hi 1" Vcoil
- 8 ohms
- 200 Watts Max
- USB/FM/BT Function
- RCA AUX Input
- Mic Priority Function
- 2 Mic / 1 Guitar Input
- 2 UHF Wireless Mic
- 96 Selectable Frequency
- Mic Echo
- 12V DC IN
- Rechargeable Battery
- 68(H) x 44(W) x 36(D)cm



HD-15PA

- 15" 2 Way Bass Reflex
- Low 2" Vcoil
- Hi 1" Vcoil
- 8 ohms
- 200 Watts Max
- USB/FM/BT Function
- RCA AUX Input / Output
- Mic Priority Function
- 2 Mic Input
- Built in 2 UHF Wireless Mic
- Mic Echo
- 12V DC IN
- Rechargeable Battery
- 67(H) x 39(W) x 34(D)cm



EON-12PA

- 12" 2 Way Bass Reflex
- Low 2" Vcoil
- Hi 1.5" Vcoil
- 8 ohms
- 200 Watts Amplifier
- USB/FM/BT Function
- XLR Line Input/Output
- RCA Input
- Mic Priority Function
- 1 Mic Input
- 2 UHF Wireless Mic
- Echo/Repeat/Delay
- 12V DC IN
- Rechargeable Battery
- 57.5(H) x 33(W) x 30(D)cm



EON-15PA

- 15" 2 Way Bass Reflex
- Low 2.5" Vcoil
- Hi 1.5" Vcoil
- 8 ohms
- 200 Watts Amplifier
- USB/FM/BT Function
- XLR Line Input/Output
- RCA Input
- Mic Priority Function
- 1 Mic Input
- 2 UHF Wireless Mic
- Echo/Repeat/Delay
- 12V DC IN
- Rechargeable Battery
- 67.5(H) x 39(W) x 34.5(D)cm



NEW!

DJX-1500

- 15" 3 Way Bass Reflex
- Low -15" with 2" Vcoil
- Mid -5" with 1" Vcoil
- Hi -Horn with 1" Vcoil
- 8 ohms
- 800 Watts Max
- USB/FM/BT Function
- RCA AUX Input / Output
- Mic Priority Function
- 1 Mic / 1 Guitar Input
- 2 UHF Wireless Mic with 96 selectable freq.
- Mic Echo, Repeat, Delay
- 12V DC IN
- Rechargeable Battery
- 103(H) x 45(W) x 32.5(D)cm



MSR-15

- 15" 2 Way Bass Reflex
- Low 2.5" Vcoil
- Hi 1.7" Vcoil
- 800 Watts
- 8 Ohms
- 100dB
- 38Hz-20KHz

NEW!

MSR-15D

- Class D 500 Watts Amplifier
- DSP Management Control
- USB/BT Function
- XLR Line Input/Output
- 1 Mic Input
- RCA Input
- 72(H) X 45(W) X 42.5(D)cm





PLASTIC MOLDED SPEAKERS

ZLX SERIES



ZLX-8

- 8" 2 Way Bass Reflex
- Low 1.5" Vcoil
- Hi 1" Vcoil
- 250 Watts
- 8 Ohms
- 96dB
- 50Hz-20KHz



ZLX-10

- 10" 2 Way Bass Reflex
- Low 2" Vcoil
- Hi 1" Vcoil
- 350 Watts
- 8 Ohms
- 97dB
- 48Hz-20KHz



ZLX-12

- 12" 2 Way Bass Reflex
- Low 2.5" Vcoil
- Hi 1.7" Vcoil
- 700 Watts
- 8 Ohms
- 98dB
- 45Hz-20KHz



ZLX-15

- 15" 2 Way Bass Reflex
- Low 3" Vcoil
- Hi 1.7" Vcoil
- 1000 Watts
- 8 Ohms
- 99dB
- 43Hz-20KHz

ZLX-8D

- Class D Amplifier 250 Watts
- DSP Management Control
- USB/BT Function
- 1 Mic / Line Input (switchable)
- Mic / Guitar Input
- RCA Input
- XLR Line Output
- 43(H) X 28(W) X 24(D)cm

ZLX-10D

- Class D Amplifier 300 Watts
- DSP Management Control
- USB/BT Function
- 1 Mic / Line Input (switchable)
- Mic / Guitar Input
- RCA Input
- XLR Line Output
- 50(H) X 31(W) X 26(D)cm

ZLX-12D

- Class D Amplifier 500 Watts
- DSP Management Control
- USB/BT Function
- RCA / XLR Line Input
- 1 Mic / Line Input (switchable)
- XLR Line Output
- 62(H) X 39(W) X 34(D)cm

ZLX-15D

- Class D Amplifier 500 Watts
- DSP Management Control
- USB/BT Function
- RCA / XLR Line Input
- 1 Mic / Line Input (switchable)
- XLR Line Output
- 71(H) X 45(W) X 38(D)cm





PLASTIC MOLDED SPEAKER

WAVE SERIES



WAVE-12

- 12" 2 Way
- Bass Reflex
- Low 2" Vcoil
- Hi 1.5" Vcoil
- 500 Watts
- 8 Ohms
- 98dB
- 55Hz-20KHz
- 59(H) X 39(W) X 32(D)cm



WAVE-15

- 15" 2 Way
- Bass Reflex
- Low 2.5" Vcoil
- Hi 1.7" Vcoil
- 800 Watts
- 8 Ohms
- 100dB
- 45Hz-20KHz
- 69(H) X 45(W) X 38(D)cm

FLEX SERIES



FLEX-8

- 8" 2 Way Bass Reflex
- Low 1.5" Vcoil
- Hi 1" Vcoil
- 250 Watts
- 8 Ohms
- 96dB
- 48Hz-20KHz
- 42(H) X 27(W) X 23(D)cm



FLEX-10

- 10" 2 Way Bass Reflex
- Low 2" Vcoil
- Hi 1" Vcoil
- 350 Watts
- 8 Ohms
- 97dB
- 45Hz-20KHz
- 51(H) X 31(W) X 27(D)cm



FLEX-12

- 12" 2 Way Bass Reflex
- Low 2.5" Vcoil
- Hi 1.7" Vcoil
- 700 Watts
- 8 Ohms
- 98dB
- 43Hz-20KHz



FLEX-15

- 15" 2 Way Bass Reflex
- Low 3" Vcoil
- Hi 1.7" Vcoil
- 1000 Watts
- 8 Ohms
- 98dB
- 40Hz-20KHz

FLEX-12D

- Class D Amplifier 500 Watts
- DSP Management Control
- USB/BT Function
- RCA / XLR Line Input
- 1 Mic / Line Input (switchable)
- XLR Line Output
- 60(H) X 38(W) X 32(D)cm

FLEX-15D

- Class D Amplifier 500 Watts
- DSP Management Control
- USB/BT Function
- RCA / XLR Line Input
- 1 Mic / Line Input (switchable)
- XLR Line Output
- 72 (H) X 46(W) X 39(D)cm

