



PROFESSIONAL STAGE SPEAKER SYSTEM

SRX 800 SERIES



SRX-812

- 12" 2 way Bass Reflex
- Low 3" Vcoil
- Hi 1.7" Vcoil
- 1000 Watts
- Exit 1"
- 8 ohms
- 98dB SPL
- 90 X 60 Dispersion



SRX-815

- 15" 2 way Bass Reflex
- Low 3" Vcoil
- Hi 1.7" Vcoil
- 1000 Watts
- Exit 1"
- 8 ohms
- 99dB SPL
- 90 X 60 Dispersion

SRX-812A (ACTIVE)

- Class D
- 600 Watts Amplifier
- XLR Line Input/Output

SRX-815A (ACTIVE)

- Class D
- 600 Watts Amplifier
- XLR Line Input/Output



SRX-825

- Dual 15" Bass Reflex
- Low 3" Vcoil
- Hi 3" Vcoil
- 2200 Watts
- Exit 1.5"
- 4 ohms
- 105dB SPL
- 90 X 60 Dispersion

SRX-825A(ACTIVE)

- Class D
- 1200 Watts Amplifier
- XLR Line Input/Output



SRX-818S

- 18" Sub Bass
- Low 4" Vcoil
- 1000 Watts
- 8 ohms
- 99dB SPL
- Freq. Resp.: 38Hz-200Hz

SRX-818SA (ACTIVE)

- Class D
- 1200 Watts Amplifier
- XLR Line Input/Output
- Low Pass filter 30Hz-300Hz
- Phase Adjust: 0-180 Degrees



SRX-828S

- Dual 18" Sub Bass
- Low 4" Vcoil
- 2000 Watts
- 4 ohms
- 103dB SPL
- Freq. Resp.: 32Hz-200Hz

SRX-828SA (ACTIVE)

- Class D
- 2 x 1200 Watts Amplifier
- XLR Line Input/Output
- RJ45 (Software Adjust Parameter)





PROFESSIONAL STAGE SPEAKER

PRX SERIES



PRX-712M

- 12" 2 way Bass Reflex
- Low 2.5" Vcoil
- Hi 1.5" Vcoil
- Exit 1"
- 800 Watts
- 8 ohms
- 97dB SPL
- 90 X 60 Dispersion

PRX-712A

- 350 Watts Amplifier
- XLR Line Input/Output
- Mic Input
- Bass & Treble control



PRX-718S (Passive)

- 18" Sub Bass
- Low 4" Vcoil
- 800 Watts
- 8 ohms
- 101dB SPL
- Freq. Resp.: 40Hz - 200Hz

PRX-718SD (Active)

- Class D
- 1200 Watts Amplifier
- XLR Line Input/Output
- Low Pass filter 30Hz - 300Hz
- Phase Adjust: 0 - 180 Degrees



PRX-715M

- 15" 2 way Bass Reflex
- Low 2.5" Vcoil
- Hi 1.5" Vcoil
- Exit 1"
- 800 Watts
- 8 ohms
- 98dB SPL
- 90 X 60 Dispersion

PRX-715A

- 350 Watts Amplifier
- XLR Line Input/Output
- Mic Input
- Bass & Treble control



PRX-725 (Passive)

- Dual 15" Bass Reflex
- Low 2.5" Vcoil
- Hi 1.7" Vcoil
- Exit 1"
- 1400 Watts
- 4 ohms
- 102dB SPL
- Freq. Resp.: 50Hz - 20KHz
- 90 X 60 Dispersion

PRX-725D (Active)

- Class D
- 1200 Watts Amplifier
- XLR Line Input/Output
- High Pass Filter: 30Hz - 150Hz
- Powerkon Blue/White

