



ALL WEATHER PROOF AND MONITOR SPEAKERS



AWS-104TB AWS-104TW (Waterproof)

- 4" 2 Way Full Range
- IP46 Rating
- Impedance: 16Ω
- Sensitivity: 88dB
- Freq. Resp.: 75Hz-20KHz
- Max Power: 100W
- 100V Tap: 40,20,10W



AWS-106TB AWS-106TW (Waterproof)

- 6.5" 2 Way Full Range
- IP46 Rating
- Impedance: 16Ω
- Sensitivity: 89dB
- Freq. Resp.: 60Hz-20KHz
- Max Power: 200W
- 100V Tap: 80,40,20W



M12A (ACTIVE)

- 12" Monitor Speaker System
- Class D Amplifier
- 600 Watts Power
- Low 3" Vcoil
- Hi 1.7" Vcoil
- 8 ohms
- 97 dB SPL
- Freq. Resp.: 67Hz-20KHz



AWS-8 (Waterproof)

- 8" 2 Way Coaxial Speaker
- IP56 Rating
- Impedance: 8Ω
- Sensitivity: 96dB
- Freq. Resp.: 80Hz-18KHz
- Power: 40,80,150W
- 8Ω 200W



AWS-12 (Waterproof)

- 12" 2 Way Coaxial Speaker
- IP56 Rating
- Impedance: 8Ω
- Sensitivity: 96dB
- Freq. Resp.: 55Hz-18KHz
- Power: 50,100,200W
- 8Ω 300W



M15A (ACTIVE)

- 15" Monitor Speaker System
- Class D Amplifier
- 600 Watts Power
- Low 3" Vcoil
- Hi 1.7" Vcoil
- 8 ohms
- 98 dB SPL
- Freq. Resp.: 57Hz-20KHz





WALL MOUNT SPEAKER & PAGING MIC



WS-605T

- 6.5" 2 Way bass Reflex
- Impedance: 8 ohms
- Sensitivity: 91dB
- Freq. Resp.: 65Hz-20KHz
- Max Power: 200W
- 100V TAP 40, 20, 10, 5W
- 31(H) x 22(W) x 20(D)cm



WSL-62T

- 6.5" 2 Way bass Reflex
- Impedance: 8 ohms
- Sensitivity: 98dB
- Freq. Resp.: 160Hz-18KHz
- 100V TAP 10W, 6W, 3W
- 18(H) x 16(W) x 12(D)cm



WS-5T

- 5" 2 Way Bass Reflex
- Impedance: 8 ohms
- Sensitivity: 90dB
- Freq. Resp.: 80Hz-20KHz
- Max Power: 150W
- 100V TAP 30, 15, 8, 4W
- 28(H) x 17(W) x 15(D) cm



CLM-301T

- 4 X 3" & 1" Dome Tweeter
- Water Proof Aluminum Housing
- Sensitivity: 93dB
- Freq. Resp.: 90Hz-20KHz
- Equipped with bracket
- 100V TAP 60, 30, 15, 8W
- 60(H) x 11(W) x 10(D)cm



WS-6T

- 6.5" 2 Way bass Reflex
- Impedance: 8 ohms
- Sensitivity: 91dB
- Freq. Resp.: 65Hz-20KHz
- Max Power: 200W
- 100V TAP 30, 15, 8, 4W
- 38(H) x 21(W) x 19(D)cm



CM-100UR (Paging Microphone)

- Transducer type: Condenser
- Freq. Resp.: 40Hz-15KHz
- Output Impedance: 200Ω
- Polar Pattern: Supercardioid
- Power Supply: Dc 12V, 4.5V (AA)
- USB (MP3 & REC function)
- With Chime function

